

Hydro-Mobile **P** Series

Best lift capacity-speed balance !

Smaller scale platforms for restrained areas. Ideal for narrow shafts and indoor jobs. Unit easily fits through 34" door.

Motorized unit

Configuration of 1 m (3') to 8.3 m (27'), lifting capacity of up to 2 700 kg (6 000 lbs)




P Series: Features & Benefits

- Sized-down design for restrained areas
- Quick installation
- Straightforward, low maintenance lift mechanism

ACCESSORIES

MODULAR BRIDGES
Width 1.52 m (5')



HFBG60
1.52 m (5')



HFBG30
0.76 m (30")



HFBG60EX
0.76 m (30")
Bridge Extension



HFBG-BEA
Support bridge

Twin motorized units:
Configuration of 3 m (10') to 24 m (79'), lifting capacity of up to 4 536 kg (10 000 lbs)

Specifications	M	F	P	E
Max. lifting capacity	9 090 kg (20 000 lbs)	5 450 kg (12 000 lbs)	2 730 kg (6 000 lbs)	2 600 kg (5 800 lbs)
Lift speed	1 m/min (3'/min)	11.5 m/min (38'/min)	3 m/min (10'/min)	6.4 m/min (21'/min)
Motor power source	Fuel	Fuel, electricity	Fuel, electricity, propane	Electricity
Single unit				
Min. length	7.3 m (24')	3 m (10')	1 m (3')	4.3 m (14')
Max. length	18.3 m (60')	15.2 m (50')	8.2 m (27')	12 m (39')
Twin unit				
Max. length	42 m (138')	35 m (115')	25 m (83')	30 m (98')
Floor deck				
Min. width	2.1 m (7')	1.53 m (5')	1.53 m (5')	1.53 m (5')

Hydro-Mobile **P** Series

P on wheels



Hoist



Pedestrian underpass for P-F-M2

